2" INGROUND - SLIM ROUND





LANDSCAPE LIGHTING







Location:

SPECIFICATIONS

Brightness: 170 lm **Beam Angle:** 25°

85

Input:

Power:

CRI:

Rated Life:

Fixture Type:	
Catalog Numbe	r:
Project:	

PRODUCT DESCRIPTION

Landscape 2" recessed inground luminaire for soft ground application.

FEATURES

- IP68 rated, Suitable for continuous immersion under water
- Factory sealed water tight fixtures
- Solid stainless steel construction
- 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

ORDERING NUMBER

	Co	Color Temp	Finish	
2011 Slim	round 27	2,001		Bronzed Stainless Steel Stainless Steel

IEC safety Standard	Walk over	Drive over	
Resistance to static load test	Yes (1125lbs)	Yes (4496lbs)	
Resistance to torque and shear loads test	N/A	Yes	

9 - 15VAC (Transformer is required)

4.1W / 6.6VA

70,000 hours

2011-30Example: **2011-30SS**

2" INGROUND - SLIM ROUND





Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS *75W Max*

9150-TRN-SS *150W Max*

9300-TRN-SS 300W Max

9600-TRN-SS 600W Max



TESTED MAGNETIC LOW VOLTAGE(MLV) DIMMERS

Luminaire	Dimmer						
	Manufacturer	Family	Model	Power Rating	Range*	Note	
	Lutron	Diva	DVLV-600	600W	20% - 100%		
2011		Skylark	SLV-600P	600W	15% - 100%	Best performance	
		Skylark	S-10P	1000W		Not recommended	

^{*}Low end of this range is determined by output current which may not directly translate to the perceived light output

WAC Lighting fixtures are compatible with a variety of dimmers. For your convenience we have included a compatibility chart showing dimmers which have been tested with our products. The recommended list below is based upon testing conducted in a lab, and the results can vary in certain field applications due to a number of factors. Exclusion from the list does not imply incompatibility, just that it has not been tested by WAC Lighting. Please reference the dimmer manufacturer's instructions for installation, or contact a WAC lighting professional at 800-526-2588.