OCULUX ARCHITECTURAL 2" MULTIPLE SPOTS

2 LIGHT BEVEL - MT-22DT, MT-22DL

WAC LIGHTING

Responsible Lighting®

	Fixture Type:	
AA	Catalog Number:	
	Project:	
	Location:	

PRODUCT DESCRIPTION

With a smaller aperture and shallow housing height, Oculux Architectural 2" Multiples offer performance features in a simple but versatile package for residential and commerical applications alike. The rare earth magnetic mounting makes for ease of installation and service. Universal housing can be used with trim or trimless, while delivering downlighting, adjustability, and pinhole lighting effects.

FEATURES

- Refined 2" aperature and shallow <4" housing
- Adjustable LED light engine included with housing: Vertical adjustment 0-40°, Horizontial adjustment 0-360°
- Rare earth magnetic light engine mounting
- Accomodates accessory optical film and one lens or honeycomb louver
- Bevel and pinhole trim options
- Universal housing can be used with trim and trimless options
- · Each light engine can be independently controlled
- 5 year warranty

SPECIFICATIONS

Construction: Die-cast aluminum trim and light engine. Steel housing.

Input: 120V - 277V AC 50/60 Hz.

Dimming: 100% - 5% TRIAC, ELV (120V) 100% - 5%, 0-10V (120-277V)

Light Source: High output 3-step Mac Adam Ellipse COB

Rated life of 50,000 hrs

Mounting: Accommodates ½"-1" ceiling thickness. **Finish:** Electrostatically powder coated White, Black.

Operating temp: -4°F to 104°F (-20°C to 40°C)

Standards: UL & cUL, Wet Location listed, Title 24 JA8-2019 Compliant.

Trims (Order Housing Separately)	Model	Housing	Beam	Color Temp	CRI	Lumens	CBCP	Finish
13/16" 83/16"			Spot 16°	927 2700K 930 3000K 935 3500K 940 4000k	90 90 90 90	590 x2 620 x2 640 x2 700 x2	5150 x2 5415 x2 5565 x2 6075 x2	
3 ³ / ₈ "	MT-22DT 2 Light Trim Bevel	MT-2209 17W	Narrow Flood 30°	927 2700K 930 3000K 935 3500K 940 4000K	90 90 90 90	550 x2 600 x2 595 x2 650 x2	1485 x2 1715 x2 1665 x2 1825 x2	
			Flood 50°	927 2700K 930 3000K 935 3500K 940 4000K	90 90 90 90	665 x2 690 x2 710 x2 795 x2	870 x2 965 x2 970 x2 1095 x2	
13/4e" 10/46" 1 75/6"			Spot 16°	927 2700K 930 3000K 935 3500K 940 4000K	90 90 90 90	935 x2 1045 x2 1020 x2 1085 x2	8300 x2 9300 x2 9055 x2 9660 x2	WT White BK Black
53%" 4 27%" L	MT-22DL 2 Light Trimless Bevel	MT-2215 30V	Narrow Flood 30°	927 2700K 930 3000K 935 3500K 940 4000K	90 90 90 90	885 x2 1055 x2 950 x2 1010 x2	2405 x2 3030 x2 2660 x2 2840 x2	
			Flood 50°	927 2700K 930 3000K 935 3500K 940 4000K	90 90 90 90	1060 x2 1175 x2 1155 x2 1280 x2	1395 x2 1710 x2 1580 x2 1765 x2	

MT-22D_-_ Example: MT-22DT-WT


waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 **Western Distribution Center** 1750 Archibald Avenue Ontario, CA 91760

OCULUX ARCHITECTURAL 2" MULTIPLE SPOTS

WAC LIGHTING

2 LIGHT BEVEL - MT-22DT, MT-22DL

Responsible Lighting®



MT-22__-Example: MT-2215-S935

ACCESSORIES Each light engine accomodates accessory optical film and one lens or honeycomb louver

ACCESSORY HOLDER sold separately

LENS-11-HLD Required for use with any lens or accessory

GLARE CONTROL ACCESSORIES sold separately

LENS-11-HCL Honeycomb Louver

LENS ACCESSORIES sold separately

L	RED FR SPR	Amber Red Frosted Spread Beam Elongating

ACCESSORY OPTIC FILMS sold separately

MT-2-FII M

Optic Film Package: includes 3 films (A, B, C)					
LENS-11	LENS-11-HLD Required (sold separately)				
Primary Optic	Accessory Film	Resulting Beam			
S (16°)	Α	25°			
S (16°)	В	45°			
S (16°)	С	55°			
N (30°)	А	35°			
N (30°)	В	55°			
N (30°)	С	65°			
F (50°)	А	52°			
F (50°)	В	70°			
F (50°)	С	80°			





COVERAGE DIAMETER	FROM 8' CEILING IN FEET
--------------------------	-------------------------

Primary Optic	No Film	+ Film A	+ Film B	+ Film C
Spot	2'	3.5′	6.5′	8.5′
Narrow	4.5'	5′	8.5′	10'
Flood	7.5′	8'	11'	13.5′

COVERAGE DIAMETER FROM 10' CEILING IN FEET

Primary Optic	No Film	+ Film A	+ Film B	+ Film C
Spot	3′	4.5'	8.5′	10.5′
Narrow	5.5′	6.5′	10.5′	12.5′
Flood	9.5′	10'	14'	17′

Above charts represent beam distribution only. Footcandle values should be considered in addition to meet project requirements.

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 **Western Distribution Center** 1750 Archibald Avenue Ontario, CA 91760

OCULUX ARCHITECTURAL 2" MULTIPLE SPOTS

2 LIGHT BEVEL - MT-22DT, MT-22DL



Responsible Lighting®

REPLACEMENT HEADS (INCLUDES: ONE HEAD & LED)

Model	Beam	Color Temp
4MT2-S927-BK 4MT2-S930-BK 4MT2-S935-BK 4MT2-S940-BK	Spot	2700K 3000K 3500K 4000K
4MT2-N927-BK 4MT2-N930-BK 4MT2-N935-BK 4MT2-N940-BK	Narrow Flood	2700K 3000K 3500K 4000K
4MT2-F927-BK 4MT2-F930-BK 4MT2-F935-BK 4MT2-F940-BK	Flood	2700K 3000K 3500K 4000K

REPLACEMENT DRIVERS (ONE DRIVER PER LIGHT ENGINE)

Model	Power	Rating
D-MT2-9	8.5W	IC
D-MT2-15	15W	Non-IC