INSTALLATION INSTRUCTION

809 Low Voltage LED Track Luminaires

HHT-809LED, LHT-809LED, JHT-809LED

WAC LIGHTING

Responsible Lighting®

CAUTION:

Read all instructions before installing.

Switch off power before installing or re-lamping.

Do not attempt to energize anything other than a track light fixture.

All installation shall be in accordance with NEC and all local codes.

OVERVIEW:

Fixtures are designed for use on on WAC "L", "H", "J" series track. They may also be used on other manufacturer's brand of track (consult factory for compatibility).

LAMPING:

- 1. Use dimmable MR16 LED lamp (included)
- 2. Remove the check ring.
- 3. Insert the MR16 lamp by aligning the pins with the holes in the ceramic socket, and pushing straight in.
- 4. Re-install the check ring.

FIXTURE INSTALLATION

- 1. Note the track has a groove running its length to indicate polarity.
- 2. Note the slant of the locking tab.
- 3. Insert adapter into track slot and rotate adaptor 90° so that the low side of the locking tab faces the grooved side of the track.
- 4. Make sure the locking tab seats in the track slot.
- 5. Removal is the reverse procedure. Track heads may be positioned anywhere along the track length.
- 6. Not suitable for use on wall mounted track.





