

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Spa Outdoor Wall Sconce 3000K

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Finish
WS-W41716 16"	3000K 90	12.4W	375	185	BZ Bronze

Example: **WS-W41716-BZ**

DESCRIPTION

A dazzling and shimmering sparkle of light, Spa features a hand poured pane of art glass that creates beautiful and dramatic patterns of light when illuminated. Built with solid die-cast aluminum hardware that is weather resistant with a powder coated finish. The light engine is factory sealed for maximum protection against the harshest elements.

FEATURES

- Hand poured pane of art glass creates beautiful, dramatic patterns of light
- Weather resistant powder coated finish
- Light engine is factory sealed for maximum protection from the elements
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100 - 10%
Rated Life:	54000 Hours
Standards:	ETL, cETL, IP65 Wet Location Listed
Construction:	Aluminum hardware with glass diffuser




FINISHES



Bronze

LINE DRAWING



Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Spa Outdoor Wall Sconce 3000K

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Finish
WS-W41722 22"	3000K 90	12.5W	365	180	BZ Bronze

Example: **WS-W41722-BZ**

DESCRIPTION

A dazzling and shimmering sparkle of light, Spa features a hand poured pane of art glass that creates beautiful and dramatic patterns of light when illuminated. Built with solid die-cast aluminum hardware that is weather resistant with a powder coated finish. The light engine is factory sealed for maximum protection against the harshest elements.

FEATURES

- Hand poured pane of art glass creates beautiful, dramatic patterns of light
- Weather resistant powder coated finish
- Light engine is factory sealed for maximum protection from the elements
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100 - 10%
Rated Life:	54000 Hours
Standards:	ETL, cETL, IP65 Wet Location Listed
Construction:	Aluminum hardware with glass diffuser



FINISHES



Bronze

LINE DRAWING

