

52W EXTERMINATOR II – model: 1052

LEDme® W Track Luminaire

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

LEDme® Exterminator offers superior light output in a small, unobtrusive design. Developed for upscale residential and commercial environments.

FEATURES

- Accommodates one lens accessory and one glare control accessory
- Reflectors and LED modules can be purchased separately for alternative beam angles and color temperatures
- 365° horizontal rotation and 180° vertical aiming
- 80,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

- Construction:** Die-cast aluminum with removable front cap for easy change of lenses or accessories
- Power Consumption:** 52W
- Light Source:** High output COB LED
- Dimming:** 100%-5% Electronic Low Voltage Powder
- Finish:** coated Black, Platinum and White
- Standards:** ETL&cETL Listed, Energy Star® rated

ORDER NUMBER

System	Beam	Color Temp	CRI	Lumens	CBCP	Finish
WTK 120V	1052N 25°	827 2700K 85 3355 13451	85	3355	13451	BK Black PT Platinum WT White
		927 2700K 90 2930 11727				
		830 3000K 85 3540 14219				
		930 3000K 90 3117 12485				
		835 3500K 85 4023 16084				
		840 4000K 85 4150 15970				
	1052F 55°	827 2700K 85 3033 3795	85	3033	3795	
		927 2700K 90 2646 3425				
		830 3000K 85 3190 4231				
		930 3000K 90 2818 3513				
		835 3500K 85 3637 4546				
		840 4000K 85 3752 4640				
WHK 277V	1052N 25°	827 2700K 85 3355 13451	85	3355	13451	
		927 2700K 90 2930 11727				
		830 3000K 85 3540 14219				
		930 3000K 90 3117 12485				
		835 3500K 85 4023 16084				
		840 4000K 85 4150 15970				
	1052F 55°	827 2700K 85 3033 3795	85	3033	3795	
		927 2700K 90 2646 3425				
		830 3000K 85 3190 4231				
		930 3000K 90 2818 3513				
		835 3500K 85 3637 4546				
		840 4000K 85 3752 4640				

FLAT LENS ACCESSORIES

Amber	LENS-25-AMB
Blue	LENS-25-BLU
Green	LENS-25-GRN
Red	LENS-25-RED
Yellow	LENS-25-YEL
UV Filter	LENS-25-UVF
Frosted	LENS-25-FR
Spread	LENS-25-SPR
Beam Elongating	LENS-25-BEL

REFLECTORS

25°	SL-REF-LUX1208-N
55°	SL-REF-LUX1208-F

LED MODULES

2700K CRI 85	LHC1-2780-1208-W
2700K CRI 90	LHC1-2790-1208-W
3000K CRI 85	LHC1-3080-1208-W
3000K CRI 90	LHC1-3090-1208-W
3500K CRI 85	LHC1-3580-1208-W
4000K CRI 85	LHC1-4080-1208-W

GLARE CONTROL - CROSS LOUVER

LENS-25P-CRL-WT	White
LENS-25P-CRL-BK	Black
LENS-25P-CRL-BN	Brushed Nickel

GLARE CONTROL - SNOOT

LENS-25-SNOOT-WT	White
LENS-25-SNOOT-BK	Black
LENS-25-SNOOT-BN	Brushed Nickel



Example: WTK-1052N-827-WT

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760