


TUBE ARCHITECTURAL DS-WE08

8" Extended Single LED Wall Mount

WAC LIGHTING



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

FEATURES

- Single light extended body high performance exterior rated LED wall mount
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

| | |
|------------------------|--|
| Input: | Universal voltage 120V - 277VAC, 50/60Hz |
| Dimming: | Electronic low voltage (ELV) : 100% - 5% 0-10V: 100% - 1% |
| Light Source: | High output 3 Step Mac Adam Ellipse COB Rated life of 60,000 hours at L70 |
| Finish: | Electrostatically powder coated white, black, bronze and graphite |
| Standards: | IP65 rated, ETL & cETL wet location listed Energy Star® 2.2 Title 24 JA8-2016 Compliant |
| Operating Temp: | -13°F to 122°F (-25°C to 50°C); EM: -4°F to 122°F (-20°C to 50°C) |

ORDERING NUMBER

| Diameter | Watt | Beam | Beam Angle | Color Temp | CRI | Reference Lumen | Output ² CBCP | (lm/w) Efficacy | Light Distribution | Finish | |
|--------------------------|--------------------------|--------------------------|-------------------------|------------|-------|-----------------|--------------------------|-----------------|--------------------|--------|--|
| DS-WE08 | 46W | S Straight up or down | 18° | 927S | 2700K | 90 | 3080 | 15187 | 67 | | BK Black WT White BZ Bronze GH Graphite |
| | | | | 27S | 2700K | 85 | 3865 | 19064 | 84 | | |
| | | | | 930S | 3000K | 90 | 3275 | 16156 | 71 | | |
| | | | | 30S | 3000K | 85 | 3935 | 19387 | 86 | | |
| | | | | 35S | 3500K | 85 | 4030 | 19872 | 88 | | |
| | | | | 40S | 4000K | 85 | 4095 | 20195 | 89 | | |
| | 46W | N Straight up or down | 25° | 927S | 2700K | 90 | 3185 | 10536 | 68 | | |
| | | | | 27S | 2700K | 85 | 4000 | 13226 | 87 | | |
| | | | | 930S | 3000K | 90 | 3390 | 11208 | 74 | | |
| | | | | 30S | 3000K | 85 | 4070 | 13450 | 88 | | |
| | | | | 35S | 3500K | 85 | 4170 | 13786 | 91 | | |
| | | | | 40S | 4000K | 85 | 4240 | 14010 | 92 | | |
| DS-WE08EM ¹ | 46W | F Straight up or down | 35° | 927S | 2700K | 90 | 3015 | 5475 | 66 | | |
| | | | | 27S | 2700K | 85 | 3785 | 7211 | 82 | | |
| | | | | 930S | 3000K | 90 | 3210 | 6111 | 70 | | |
| | | | | 30S | 3000K | 85 | 3850 | 7334 | 84 | | |
| | | | | 35S | 3500K | 85 | 3945 | 7517 | 86 | | |
| | | | | 40S | 4000K | 85 | 4010 | 7639 | 87 | | |
| DS-WE0834 | 34W | F Straight up or down | 35° | 927S | 2700K | 90 | 3015 | 5475 | 66 | | |
| | | | | 27S | 2700K | 85 | 3785 | 7211 | 82 | | |
| | | | | 930S | 3000K | 90 | 3210 | 6111 | 70 | | |
| | | | | 30S | 3000K | 85 | 3850 | 7334 | 84 | | |
| | | | | 35S | 3500K | 85 | 3945 | 7517 | 86 | | |
| | | | | 40S | 4000K | 85 | 4010 | 7639 | 87 | | |
| | DS-WE0834EM ¹ | 34W | F Away from the wall | N/A | 927A | 2700K | 90 | 3020 | N/A | 66 | |
| | | | | | 27A | 2700K | 85 | 3790 | N/A | 82 | |
| | | | | | 930A | 3000K | 90 | 3210 | N/A | 70 | |
| | | | | | 30A | 3000K | 85 | 3855 | N/A | 84 | |
| | | | | | 35A | 3500K | 85 | 3950 | N/A | 86 | |
| | | | | | 40A | 4000K | 85 | 4015 | N/A | 87 | |
| DS-WE0834EM ¹ | 34W | F Towards the wall | N/A | 927B | 2700K | 90 | 3020 | N/A | 66 | | |
| | | | | 27B | 2700K | 85 | 3790 | N/A | 82 | | |
| | | | | 930B | 3000K | 90 | 3210 | N/A | 70 | | |
| | | | | 30B | 3000K | 85 | 3855 | N/A | 84 | | |
| | | | | 35B | 3500K | 85 | 3950 | N/A | 86 | | |
| | | | | 40B | 4000K | 85 | 4015 | N/A | 87 | | |

DS-WE08-_____ - _____

¹EM fixtures provided with integral emergency battery back up. Provides at least 90 minutes of 5W illumination during emergency operation. Emergency test button and indicator light located in fixture mounting arm.

Example: DS-WE08-F930A-WT

²Reference output shows 46W output. Multiply by 0.8 to determine output for 34W combinations.

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760