DECK & PATIO - TRIANGLE




LANDSCAPE LIGHTING

Fixture Type:

Catalog Number:

Project:

Location:



SPECIFICATIONS

| Input: | 9-15VAC (Transformer is required) |
|-------------|-----------------------------------|
| Power: | 2.8W / 4.6VA |
| Brightness: | 60 lm |
| CRI: | 90+ |
| Rated Life: | 50,000 hours |

PRODUCT DESCRIPTION

Deck and patio light with superb forward-throw light distribution

FEATURES

- IP66 rated, Protected against powerful water jets
- Translucent lens provides for uniform diffused light output
- Solid diecast brass or corrosion resistant aluminum alloy
- ADA compliant
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

ORDERING NUMBER

| | | Color Temp | Finish |
|------|----------|------------------------------------|--|
| 3021 | Triangle | 27 2700K 30 3000K | BBRBronze on BrassBKBlack on AluminumBZBronze on AluminumWTWhite on Aluminum |

3021-____

Example: 3021-30BZ

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. JUL 2016

tant aluminum alloy gainst voltage drop

LANDSCAPE LIGHTING

/A()

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS 75W Max **9150-TRN-SS** 150W Max **9300-TRN-SS** *300W Max* 9600-TRN-SS

600W Max



TESTED MAGNETIC LOW VOLTAGE(MLV) DIMMERS

| Luminaire | Dimmer | | | | | | |
|-----------|--------------|---------|----------|--------------|------------|-----------------------------------|--|
| | Manufacturer | Family | Model | Power Rating | Range* | Note | |
| 3021 | | Diva | DVLV-600 | 600W | 33% - 100% | Output maxes at 50% dimming level | |
| | Lutron | Skylark | SLV-600P | 600W | 28% - 100% | Output maxes at 50% dimming level | |
| | | Skylark | S-10P | 1000W | | Not recommended | |

*Low end of this range is determined by output current which may not directly translate to the perceived light output

WAC Lighting fixtures are compatible with a variety of dimmers. For your convenience we have included a compatibility chart showing dimmers which have been tested with our products. The recommended list below is based upon testing conducted in a lab, and the results can vary in certain field applications due to a number of factors. Exclusion from the list does not imply incompatibility, just that it has not been tested by WAC Lighting. Please reference the dimmer manufacturer's instructions for installation, or contact a WAC lighting professional at 800-526-2588.

Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. JUL 2016