

# WAC LIGHTING

## Lotos 4" & 6" Round

### Downlight 5CCT

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

Model	Beam	Color Temp & CRI	Lumens	Finish
R4ERDR R6ERDR	W	9CS 2700K/3000K/3500K/4000K/5000K - 90	615 725 1080 1200	BK Black WT White
		9CS 2700K/3000K/3500K/4000K/5000K - 90		
		9CS 2700K/3000K/3500K/4000K/5000K - 90		
		9CS 2700K/3000K/3500K/4000K/5000K - 90		

Example: **R4ERDR-W9CS-BK**

#### DESCRIPTION

The wafer-thin Lotos LED Recessed Kit with remote driver combines high quality light output and efficiency while eliminating the need for a large housing. This innovative design can be installed easily as a remodel or new construction with an optional frame-in kit sold separately. Lotos is available in a downlight version for general ambient lighting and an adjustable version with a gimbal that pivots 360 degrees on a hinge. Now available with 5-CCT options.

#### FEATURES


- 5-CCT Switchable between 2700K and 5000K
- Multiple LED array for uniform illumination
- Driver included
- 5 year warranty

#### SPECIFICATIONS


<b>Construction:</b>	Steel with frosted TIR lens
<b>Power:</b>	8W, 12W
<b>Input:</b>	120 -277 VAC, 50/60Hz
<b>Dimming:</b>	ELV: 100-5% , TRIAC: 100-5%
<b>Light Source:</b>	Integrated LED
<b>Lens:</b>	Translucent acrylic diffuser
<b>Rated Life:</b>	50000 Hours
<b>Mounting:</b>	Heavy gauge retention clips secures fixture to ceiling
<b>Cut Out:</b>	6 1/4", 4 1/4"
<b>Finish:</b>	Electrostatically powder coated: White, Black
<b>Ceiling Thickness:</b>	1/2" - 1"
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8 Compliant, IC, Airtight



#### FINISHES:



#### LINE DRAWING:



# WAC LIGHTING

## Lotos 4" & 6" Round Downlight 5CCT

Fixture Type: \_\_\_\_\_  
Catalog Number: \_\_\_\_\_  
Project: \_\_\_\_\_  
Location: \_\_\_\_\_

---

**ACCESSORIES**

---

<i>Model</i>	<i>Description</i>	<i>Finish</i>
--------------	--------------------	---------------

---