

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Kone

Pendant 3000K

| Model & Size | Color Temp & CRI | Watt | Voltage | LED Lumens | Delivered Lumens | Finish |
|--------------|------------------|------|-------------|------------|------------------|--|
| PD-72006 6" | 3000K 90 | 11W | 120-277 VAC | 1000 | 243 | AB Aged Brass BK Black SN Satin Nickel |

Example: **PD-72006-AB**

DESCRIPTION

Minimal and inventive. A simple, conical design.

FEATURES


- Thin powered cables provide an ultra-clean look
- Driver concealed within the canopy
- Can be mounted on a sloped ceiling
- Title 24 option (special order) available with 0-10V dimming
- Quick install canopy with Title 24 option (special order) only
- 5 Year warranty

SPECIFICATIONS

| | |
|---------------|------------------------------------|
| Color Temp: | 3000K |
| Input: | 120-277 VAC, 50/60Hz |
| CRI: | 90 |
| Dimming: | ELV: 100-10%, TRIAC: 100-5% |
| Rated Life: | 50000 Hours |
| Standards: | ETL, cETL |
| | Damp Location Listed |
| Construction: | Aluminum hardware with PC diffuser |



FINISHES



LINE DRAWING

