

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Elektron Semi-Flush Mount 3000K

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Finish
FM-21720 20"	3000K 90	20W	1680	1315	AL Brushed Aluminum BK Black

Example: **FM-21720-AL**

DESCRIPTION

Travelling at the speed of light.

FEATURES

- Uniquely versatile fixture capable of transforming before your eyes
- Side lit acrylic diffuser with discretely hidden LEDs.
- downrods can be removed to mount as a ceiling fixture or wall sconce
- Three 12" and one 6" downrods included (additional downrods available)
- Driver installed within the Junction Box, driver dimension: 2.76" x 1.26" x 1.18"
- 5 Year warranty

SPECIFICATIONS

Color Temp:	3000K
Input:	120-277 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100-10%
Rated Life:	36000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, Title 24: 2019 Damp Location Listed
Construction:	Aluminum hardware with etched acrylic diffuser, Aluminum hardware with acrylic diffuser

REPLACEMENT PARTS


RPL-ROD-OUT06-AL - 6" rod - AL finish
 RPL-ROD-OUT12-AL - 12" rod - AL finish
 RPL-ROD-IN06-BK - 6" rod - BK finish
 RPL-ROD-IN12-BK - 12" rod - BK finish



FINISHES



LINE DRAWING



Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Elektron Semi-Flush Mount 3000K

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Finish
FM-21728 28"	3000K 90	30W	2525	1720	AL Brushed Aluminum
		30W	2525	1723	BK Black

Example: **FM-21728-AL**

DESCRIPTION

Travelling at the speed of light.

FEATURES

- Uniquely versatile fixture capable of transforming before your eyes
- Side lit acrylic diffuser with discretely hidden LEDs.
- downrods can be removed to mount as a ceiling fixture or wall sconce
- Three 12" and one 6" downrods included (additional downrods available)
- Driver installed within the Junction Box, driver dimension: 2.76" x 1.26" x 1.18"
- 5 Year warranty

SPECIFICATIONS


Color Temp:	3000K
Input:	120-277 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100-10%
Rated Life:	36000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, Title 24: 2019 Damp Location Listed
Construction:	Aluminum hardware with etched acrylic diffuser, Aluminum hardware with acrylic diffuser

REPLACEMENT PARTS

- RPL-ROD-OUT06-AL - 6" rod - AL finish
- RPL-ROD-OUT12-AL - 12" rod - AL finish
- RPL-ROD-IN06-BK - 6" rod - BK finish
- RPL-ROD-IN12-BK - 12" rod - BK finish



FINISHES



LINE DRAWING

