

# WAC LIGHTING

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Lithium Ceiling and Wall Mount

Model & Size	Color Temp & CRI	Lumens	Finish	Emergency Backup Battery
-FM-200111	2700K/3000K/3500K /4000K/5000K	1080	BN Brushed Nickel	Emergency Backup
-FM-200115		1815	BN Brushed Nickel	
-FM-200115EM		2410	BN Brushed Nickel	
-FM-200118				
-FM-200118EM				

Example: **FM-200111-CS-BN**

### DESCRIPTION

Multiple high-powered LEDs illuminate the acrylic diffuser uniformly without socket shadows which are common in conventional flush mounts.

### FEATURES

- 5-CCT Switchable between 2700K and 5000K
- Multiple LED array for uniform illumination
- Emergency Battery Backup in case of loss of power
- Driver concealed within the fixture
- 5 year warranty

### SPECIFICATIONS

Construction:	Extruded aluminum with Acrylic Diffuser
Power:	15W, 25W, 31W
Input:	120-277 VAC, 50/60Hz
Dimming:	TRIAC: 100-5%, ELV: 100-10%
Light Source:	Integrated LED
Lens:	Translucent acrylic diffuser
Rated Life:	50000 Hours
Mounting:	Installs over a 3" or 4" junction box, Can be mounted on ceiling or wall in all orientations
Finish:	Electroplated Brushed Nickel
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Damp Location Listed, Energy Star 2.0, Title 24 JA8-2016 Compliant



### FINISHES



Brushed  
Nickel

### LINE DRAWING

