

# WAC LIGHTING

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Low Voltage Multiple Spots

### 1 Light LED MR16 Trim

Model	Finish
MT-116LED	WT White
MT-116LEDTL	WT/WT White/White

Example: **MT-116LED-WT/WT**

#### DESCRIPTION

Low Voltage Multiple Spots are ideal for perimeter lighting applications in smaller scale retail, commercial and hospitality environments. Square single light gimbal ring style adjustable recessed fixture, available with flanged trim or Invisible Trim, designed to sit flush with the ceiling for a clean architectural look. Housing, trim, and lamp are sold separately.

#### FEATURES

- Trim version has a 1/4" low profile, Invisible Trim sits flush to ceiling
- The supplied clear glass lens can be replaced by a variety of lenses or accessories
- 5 year warranty

#### SPECIFICATIONS


Construction:	Stamped metal trim
Power:	7W
Light Source:	LED MR16 ( Included )
Cut Out:	Trimless : 5 5/8" x 5 5/8", Trim : 5 3/16" x 5 3/16"
Finish:	Electrostatically Powder Coated White, White/White
Standards:	UL, cUL, Damp Location Listed




#### FINISHES



#### LINE DRAWING



Trim



Invisible Trim™

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_







Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Low Voltage Multiple Spots

1 Light LED MR16 Trim

### ACCESSORIES

	<i>Model</i>	<i>Description</i>	<i>Finish</i>
	<b>LENS-16-AMB</b> <b>LENS-16-BLU</b> <b>LENS-16-GRN</b> <b>LENS-16-RED</b>	<i>Colored Lens</i> <i>Colored Lens</i> <i>Colored Lens</i> <i>Colored Lens</i>	<i>Amber</i> <i>Blue</i> <i>Green</i> <i>Red</i>
	<b>LENS-16-FR</b>	<i>Clear/Frosted Lens</i>	<i>Frosted</i>
	<b>LENS-16-SPR</b>	<i>Spread Lens</i>	<i>Spread Lens</i>
	<b>LENS-16-UVF</b>	<i>UV Filter lens</i>	<i>Clear</i>
	<b>LENS-16-BEL</b>	<i>Beam Elongating Lens</i>	<i>Beam Elongating</i>
	<b>LENS-16-HCL</b>	<i>Honeycomb Louver</i>	<i>Black</i>

# WAC LIGHTING

## Low Voltage Multiple Spots 1 Light Housing

### Model & Product

MT-116HS Low Voltage Multiple Single Light Non-IC Housing

Example: **MT-116HS**

### DESCRIPTION

Low Voltage Multiple Spots are ideal for perimeter lighting applications in smaller scale retail, commercial and hospitality environments. Square single light gimbal ring style adjustable recessed fixture, available with flanged trim or Invisible Trim, designed to sit flush with the ceiling for a clean architectural look. Housing, trim, and lamp are sold separately.

### FEATURES

- Electronic short circuit and overload protection with automatic reset
- Soft start to prolong lamp life
- Transformer concealed within the fixture
- 5 year warranty

### SPECIFICATIONS


<b>Construction:</b>	Aluminum hardware with mouth blown etched glass diffuser
<b>Input:</b>	120 VAC, 50/60Hz
<b>Dimming:</b>	ELV: 100-10%
<b>Light Source:</b>	Halogen or LED MR16
<b>Mounting:</b>	Supplied with hanger bars, adjustable from 15"-24 1/2" to accommodate various joist construction and grid sizes
<b>Ceiling Thickness:</b>	1/2" - 1"
<b>Standards:</b>	UL, cUL, Damp Location Listed, Non IC

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_



### LINE DRAWING

