

R4FRWT

4" FQ - Round Wall Wash Trim



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 45° vertical tilting and 360° horizontal rotation, and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

FEATURES

- Two-piece die-cast construction
- Light engine mounted on trim with springs for easy replacement
- 365° horizontal rotation
- Designed for even wall illumination both vertically and horizontally
- 5 year WAC Lighting product warranty

SPECIFICATIONS

- Construction:** Durable die-cast aluminum construction
- Input:** Universal 120-277V AC 50/60 Hz
- Dimming:** Electronic Low Voltage (ELV): 100%-1%
TRIAC: 100%-1%
0-10V: 100-1%
- Light Source:** High output 3-step Mac Adam Ellipse COB
Rated life of 50,000 hours at L70
- Mounting:** Heavy gauge retention clips support trim firmly. Safety cabling standard. Ceiling cutout: Ø 4 3/4" Accommodates 1/2" - 1" ceiling thickness
- Finish:** Electrostatically powder coated White, Black, Dark Bronze. Enamel coated Haze.
- Standards:** ETL & cETL Wet Location Listed, Title 24 JA8 Compliant.

	Model	Beam	*Lumens	*CBCP	Color Temp	CRI	Finishes	Reflector/Trim
	R4FRWT Round Trim	A Asym	1845	N/A	927 2700K	90	BK DB HZWT WT	Black Dark Bronze Haze/White White
			1940	N/A	930 3000K	90		
			1980	N/A	935 3500K	90		

R4FRWT-__-__

Example: **R4FRWT-930-WT**

*Lumens shown in the table are reference values for 3000K trim with 4 housing. Use multiplier table below to determine the output for other combinations.

Multiplier		TRIM		
		927	930	935
HOUSING	4	0.95	1.00	1.02
	3	0.84	0.88	0.90
	2	0.65	0.68	0.70
	1	0.45	0.47	0.48

Example: **R4FRWT-930-WT** with 1 housing: 1940 lm (Reference Output) x 0.47 (Multiplier) = 910 lm

Please see next page for housing units(required)

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center




1750 Archibald Avenue

Ontario, CA 91761

R4FRWT

4" FQ - Round Wall Wash Trim



HOUSING (Required)	Model	Power	Emergency Backup
<p>New Construction IC Airtight</p> 	<p>R4FBNT</p>	<p>1 13W IC 2 19W IC 3 25W IC 4 28W Non-IC</p>	<p>EM Optional</p>
<p>New Construction Frame-in Non-IC</p> 	<p>R4FBFT</p>	<p>1 13W Non-IC 2 19W Non-IC 3 25W Non-IC 4 28W Non-IC</p>	<p>EM Optional</p>
<p>Remodel Non-IC</p> 	<p>R4FBRT</p>	<p>1 13W Non-IC 2 19W Non-IC 3 25W Non-IC 4 28W Non-IC</p>	<p>N/A</p>

R4FB ____ - ____

Example: **R4FBNT-3** or **R4FBNT-3-EM** (with Emergency backup battery)

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91761