

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Interlace

Pendant 3000K

| Model & Size | Color Temp | Finish                | LED Watts | LED Lumens | Delivered Lumens |
|--------------|------------|-----------------------|-----------|------------|------------------|
| PD-47828 28" | 3000K      | BK Black<br>CH Chrome | 57W       | 4853       | 3263             |

Example: **PD-47828-CH**

For custom requests please contact [customs@wacighting.com](mailto:customs@wacighting.com)

### DESCRIPTION

Delicate bands of light weave playfully in and out on this flowing modern design. A continuous construction, a flexible diffuser, and powered aircraft cable suspension complete an overall clean, seamless look.

### FEATURES

- Two seamless interlocked loops
- Thin powered cables provide an ultra-clean look
- Can be mounted on a sloped ceiling
- Driver concealed within the canopy
- 5 year warranty

### SPECIFICATIONS


|               |  |
|---------------|--|
| Color Temp:   | 3000K  |
| Input:        | 120-277 VAC,50/60Hz  |
| CRI:          | 90   |
| Dimming:      | ELV: 100-10% , 0-10V: 100-5%                                   |
| Rated Life:   | 54000 Hours  |
| Standards:    | ETL, cETL, Title 24 JA8-2019 Compliant<br>Damp Location Listed |
| Construction: | Aluminum body with flexible composite diffuser                 |



### FINISHES:



### LINE DRAWING:



Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Interlace

Pendant 3000K

| Model & Size | Color Temp | Finish                | LED Watts | LED Lumens | Delivered Lumens |
|--------------|------------|-----------------------|-----------|------------|------------------|
| PD-47839 39" | 3000K      | BK Black<br>CH Chrome | 57W       | 4734       | 3241             |

Example: **PD-47839-CH**

For custom requests please contact [customs@waclighting.com](mailto:customs@waclighting.com)

### DESCRIPTION

Delicate bands of light weave playfully in and out on this flowing modern design. A continuous construction, a flexible diffuser, and powered aircraft cable suspension complete an overall clean, seamless look.

### FEATURES


- Two seamless interlocked loops
- Thin powered cables provide an ultra-clean look
- Can be mounted on a sloped ceiling
- Driver concealed within the canopy
- 5 year warranty

### SPECIFICATIONS

|               |  |
|---------------|--|
| Color Temp:   | 3000K  |
| Input:        | 120-277 VAC, 50/60Hz   |
| CRI:          | 90   |
| Dimming:      | ELV: 100-10% , 0-10V: 100-5%                                   |
| Rated Life:   | 54000 Hours  |
| Standards:    | ETL, cETL, Title 24 JA8-2019 Compliant<br>Damp Location Listed |
| Construction: | Aluminum body with flexible composite diffuser                 |



### FINISHES:



Black

Chrome

### LINE DRAWING:

