

WAC LIGHTING

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

1" LEDme®

Round Open Reflector Downlight (Remote Driver)

Model	Color Temp & CRI	Lumens	CBCP	Finish
HR-LED231R	27 2700K - 85	255	539	BN Brushed Nickel
	30 3000K - 85	260	550	GM Gun Metal
	35 3500K - 85	275	584	WT White
	40 4000K - 85	295	619	

Example: **HR-LED231R-27-BN**

DESCRIPTION

Perfect for ceilings, under cabinet and wall niches. LED Miniature Recessed Downlights offer a super low profile and Die-cast aluminum trim with a 25° cutoff angle for comfortable general and task lighting.

FEATURES


- Round recessed trim with interior open reflector for use with a remote driver
- Driver Required: LD-700MA03-EDIM-IS or LD-700MA09-EDIM-IS
- Driver required
- 5 year warranty

SPECIFICATIONS

Construction:	Die-cast aluminum trim, aluminum heat sink and 20 gauge steel housing painted black.
Power:	3W
Input:	50/60Hz
Dimming:	ELV: 100-10%
Light Source:	Integrated LED
	3 Step Mac Adam Ellipse
Rated Life:	80000 Hours
Mounting:	Heavy gauge retention clips secures housing firmly to ceiling
Cut Out:	2 1/2"
Finish:	Electrostatically Powder Coated White, Electroplated Brushed Nickel, Electroplated Gun Metal
Ceiling Thickness:	1/2" - 1"
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Damp Location Listed, NON IC



FINISHES



LINE DRAWING

