

# WAC LIGHTING

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## 1" LEDme®

### Square Open Reflector Downlight w/ Integral Driver

Model	Color Temp & CRI	Lumens	CBCP	Finish
HR-LED251E	27 2700K - 85	245	530	BN Brushed Nickel
	30 3000K - 85	250	540	GM Gun Metal
	35 3500K - 85	270	573	WT White
	40 4000K - 85	285	608	

Example: **HR-LED251E-27-BN**

#### DESCRIPTION


Perfect for ceilings, under cabinet and wall niches. LED Miniature Recessed Downlights offer a super low profile and Die-cast aluminum trim with a 25° cutoff angle for comfortable general and task lighting.

#### FEATURES


- New Construction, may be re-configured in the field for Remodel
- Driver required
- 5 year warranty

#### SPECIFICATIONS

<b>Construction:</b>	Die-cast aluminum trim, aluminum heat sink and 20 gauge steel housing painted black.
<b>Power:</b>	4W
<b>Input:</b>	120 VAC, 50/60Hz
<b>Dimming:</b>	ELV: 100-10%
<b>Light Source:</b>	Integrated LED 3 Step Mac Adam Ellipse
<b>Rated Life:</b>	80000 Hours
<b>Mounting:</b>	Heavy gauge retention clips secures housing firmly to ceiling
<b>Cut Out:</b>	2 1/2"
<b>Finish:</b>	Electrostatically Powder Coated White, Electroplated Brushed Nickel, Electroplated Gun Metal
<b>Ceiling Thickness:</b>	1/2" - 1"
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	UL, cUL, Damp Location Listed, IC



#### FINISHES



#### LINE DRAWING

